



Nyhetsbrev 2015

Vi vill tacka alla kunder för ett mycket bra 2014 och önskar er ett ännu bättre 2015.

Nu är snart 2015 här och vi har förberett oss rejält för att ge er nya möjligheter inför det nya året.

Vi har tagit in ett flertal nya typer av slangar som vi tror kommer ge er stora möjligheter.

- **EF-346** **En helt ny typ av superflexibel lackerings slang.**
- **EF-308** **En kanalspolslang som kommer att ersätta traditionella slangar av gummi. Lägre vikt, mindre slitage mycket flexibel även vid låga temperaturer.**
- **EF-624** **Vår nya blästerslang som är mycket flexibel och har en extremt bra livslängd.**
- **APC** **Detta är en antistatisk pulverslang. Används i de flesta manuella och automatiserade pulverlackeringsanläggningar. Finns i 10,11 och 12 mm ID.**
- **EF-522** **Hetvattenslang med två lager stålarmring (155 grader).**
- **EF-521** **Hetvattenslang med ett lager stålarmring (155 grader).**

Alla dessa slangar finns lagerhållna i Kungsbacka för omgående leverans!

Har ni tekniska frågor eller vill ha en offert på dessa slangar så är ni välkomna att kontakta oss på kontoret i Kungsbacka.



Newsletter 2015

We want to thank all our customers for a great 2014 and wish you an even better 2015

Now 2015 is close and we have prepared ourselves considerably to give you new opportunities for the new year.

We have taken in a number of new types of hoses that we believe will give you great opportunities.

- **EF-346** **A completely new type of super-flexible paint hose.**
- **EF-308** **A sewer jet hose that will replace traditional rubber hoses. Less weight, less wear and very flexible even at low temperatures.**
- **EF-624** **Our new sandblasting hose is very flexible and has extremely good life span.**
- **APC** **This is an anti-static powder hose. Used in most manual and automatic powder coating plants. Available in 10,11 and 12 mm ID.**
- **EF-522** **Hot water hose with two layers of steel reinforcement (155 degrees).**
- **EF-521** **Hot water hose with a layer of steel reinforcement (155 degrees).**

All these hoses are held in stock in Kungsbacka for immediate delivery!

If you have technical questions or want a quote for these hoses you are welcome to contact us at the office in Kungsbacka.

Jens Gustafsson
MD
jens@exitflex.se
+46 702 67 57 16

Jonas Ivarsson
Sales
jonas@exitflex.se
+46 300 319 70



EF-346 Supeflexibel lackeringslang / Super Flexible Paint hose

Technical Details												
PN	Dash Size	DN	Hose I.D. (Nom.)		Hose O.D. (Nom.)		Working Pressure		Min.Burst Pressure		Min. Bend Radius	
Part #			(In.)	(mm)	(In.)	(mm)	(psi)	(Bar)	(psi)	(Bar)	(mm)	(In.)
EF346-3	-3	5	3/16	4.8	0,405	10,3	5 000	350	20 000	1 400	50	2,0
EF346-4	-4	6	1/4	6.4	0,490	12.4	5 000	350	20 000	1 400	75	3,0
EF346-6	-6	10	3/8	9.5	0,620	15,7	4 350	300	17 400	1 200	100	4,0
EF346-8	-8	12	1/2	12.7	0,760	19,3	3 500	245	14 000	980	120	4,8

EF-624 Blästerslang / Sandblasting hose

Technical Details							
PN	Hose I.D. (Nom.)		Hose O.D. (Nom.)	Working Pressure		Min.Burst Pressure	
Part #	(In.)	(mm)	(mm)	(psi)	(Bar)	(psi)	(Bar)
EF624-12	3/4	19	34	175	12	525	36
EF624-16	1	25	40	175	12	525	36
EF624-20	1.1/4	32	48	175	12	525	36
EF624-24	1.1/2	38	54	175	12	525	36
EF624-32	2	51	73	175	12	525	36

EF-308 Kanalspolslang / Sewerjet hose

Technical Details												
PN	Dash Size	DN	Hose I.D. (Nom.)		Hose O.D. (Nom.)		Working Pressure		Min.Burst Pressure		Min. Bend Radius	
Part #			(In.)	(mm)	(In.)	(mm)	(psi)	(Bar)	(psi)	(Bar)	(mm)	(In.)
EF308-8	-8	12	1/2	12.7	0,810	20,6	4 000	275	16 000	1 100	80	3,2
EF308-12	-12	20	3/4	19.1	1,150	29,2	3 625	250	9 062	625	125	5,0
EF308-16	-16	25	1	25.4	1,440	36,6	3 625	250	9 062	625	150	6,0
EF308-20	-20	32	1.1/4	31.50	1,800	45,7	3 625	250	9 062	625	250	10,0

Jens Gustafsson
 MD
 jens@exitflex.se
 +46 702 67 57 16

Jonas Ivarsson
 Sales
 jonas@exitflex.se
 +46 300 319 70



EF-521 Hetvattenslang / Hotwater hose

Technical Details												
PN	Dash Size	DN	Hose I.D. (Nom.)		Hose O.D. (Max.)		Working Pressure		Min.Burst Pressure		Min. Bend Radius	
			(In.)	(mm)	(In.)	(mm)	(psi)	(Bar)	(psi)	(Bar)	(mm)	(In.)
EF521-4	-4	6	1/4	6.4	0,528	13.4	5 220	360	13 050	900	100	4,00
EF521-5	-5	8	5/16	8.0	0,591	15.0	4 930	340	12 325	850	115	4,60
EF521-6	-6	10	3/8	9.5	0,685	17.4	4 350	300	10 440	720	125	5,00
EF521-8	-8	12	1/2	12.7	0,811	20.6	3 625	250	9 280	640	180	7,20

EF-522 Hetvattenslang Hotwater hose

Technical Details												
PN	Dash Size	DN	Hose I.D. (Nom.)		Hose O.D. (Max.)		Working Pressure		Min.Burst Pressure		Min. Bend Radius	
			(In.)	(mm)	(In.)	(mm)	(psi)	(Bar)	(psi)	(Bar)	(mm)	(In.)
EF522-4	-4	6	1/4	6.4	0,59	15.0	9 425	650	23 200	1 600	100	4,00
EF522-5	-5	8	5/16	8.0	0,64	16.6	7 975	550	20 300	1 400	115	4,60
EF522-6	-6	10	3/8	9.5	0,75	19.0	7 610	525	19 140	1 320	125	5,00
EF522-8	-8	12	1/2	12.7	0,87	22.2	6 380	440	15 940	1 100	180	7,10

Jens Gustafsson
 MD
 jens@exitflex.se
 +46 702 67 57 16

Jonas Ivarsson
 Sales
 jonas@exitflex.se
 +46 300 319 70